IN THE CLAIMS

1. (currently amended) A method for automatically controlling the movements of at least one camera or camera lens to change the prospective of a scene viewed by said at least one camera or camera lens, said method comprising the steps of:

selecting at least one ~~known~~ sequence of camera parametrics from a plurality of ~~known~~ sequences of camera parametrics, wherein said parametrics provide instruction to control movement of said at least one camera or camera lens;

determining criteria for executing said selected ~~known~~ sequence of camera parametrics, wherein said criteria are responsive to <u>at least one</u> high level ~~parameters~~ <u>parameter of at least one object</u> contained in said scene; and

adjusting movement of said at least one camera or camera lens in response to said determined criteria.

2. (currently amended) The method as recited in claim 1 wherein said at least one ~~known~~ sequence of camera parametrics is selected from the group of camera movements including scanning, zooming, tilting, orientating, panning, fading, zoom-and- pull-back, fade-in, fade-out.

3.   (currently amended)   The method as recited in claim 1 wherein said <u>at least one</u> high level ~~parameters include~~ <u>parameter includes</u> the number of objects within said scene.

4.   (currently amended)   The method as recited in claim 1 wherein said <u>at least one</u> high level <u>parameter includes</u> ~~parameters include~~ the position of <u>at least one object</u> ~~objects~~ within said scene.

5.   (currently amended)   The method as recited in claim 1 wherein said <u>at least one</u> high level <u>parameter includes</u> ~~parameters include~~ speech recognition of <u>at least one object</u> ~~objects~~ within said scene.

6.   (currently amended)   The method as recited in claim 1 wherein said <u>at least one</u> high level <u>parameter includes</u> ~~parameters include~~ an audio ~~inputs~~ <u>input</u> of <u>at least one</u> ~~objects~~ <u>object</u> within said scene.

7.   (currently amended)   An apparatus for automatically controlling the movements of at least one camera or camera lens to change the prospective of a scene viewed by said at least one camera or camera lens, said apparatus comprising:

        a processor operative to:

receive a first input for selecting at least one ~~known~~ sequence of camera parametrics from a plurality of ~~known~~ sequences of camera parametrics, wherein said parametrics provide instruction to control movement of said at least one camera or camera lens;

receive a second input ~~consisting of~~ comprising at least one high level ~~parameters~~ parameter of at least one object contained in said scene;

determine criteria for executing said selected ~~known~~ sequence of camera parametrics, wherein said criteria are responsive to said at least one high level ~~parameters~~ parameter; and

means for adjusting movement of said at least one camera or camera lens in response to said determined criteria.

8. (currently amended) The apparatus as recited in claim ~~1~~ 7 wherein said first input is selected from the group of camera movements including scanning, zooming, tilting, orientating, panning, fading, zooming, zoom-and-pull-back, fade-in, fade-out.

9. (currently amended) The apparatus as recited in claim 7 wherein said at least one high level parameter includes~~parameters include~~ the number of objects within said scene.

10.   (currently amended)   The apparatus as recited in claim 7 wherein said at least one high level parameter includes ~~parameters include~~ the position of at least one object~~objects~~ within said scene.

11.   (currently amended)   The apparatus as recited in claim 7 wherein said at least one high level parameter includes~~parameters include~~ speech recognition of at least one ~~objects~~ object within said scene.

12.   (currently amended)   The apparatus as recited in claim 7 wherein said at least one high level parameter includes~~parameters include~~ an audio ~~inputs~~ input of at least one ~~objects~~ object within said scene.

13.   (currently amended)   The apparatus as recited in claim 7 wherein said means for adjusting said camera movement ~~includes effects~~ outputting of said criteria over a serial connection.

14.   (currently amended)   The apparatus as recited in claim 7 wherein said means for adjusting said camera movement ~~includes effects~~ outputting of said criteria over a parallel connection.

15. (currently amended) The apparatus as recited in claim 7 wherein said means for adjusting said camera movement ~~includes~~ effects outputting of said criteria over a network.

16. (original) The apparatus as recited in claim 7 wherein said camera movement is accomplished electronically.

17. (original) The apparatus as recited in claim 7 wherein said camera movement is accomplished mechanically.

18. (new) A method as in claim 1 including:
- locating the at least one object in an image of the scene;
- determining the object closet to a predetermined location in the image;
- adjusting the movement of the at least one camera or camera lens in response to said determination.

19. (new) A method as in claim 1 including:
- locating the at least one object in an image of the scene;
- determining the object closet to the center of the image;
- determining the percentage of the scene around said closest object;

—   adjusting the zoom level of the at least one camera or camera

lens in response to said percentage determination.

S:\kr\us\us01\us010002 amd1.doc   8

PAGE 8/11 * RCVD AT 7/6/2004 4:22:29 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-1/1 * DNIS:8729306 * CSID:914 332 0615 * DURATION (mm-ss):02-30